



Deutsche  
Qualität  
Garantiert



N-TYPE TOPCON TECHNOLOGY

# Terra E (CMD-72BD) 280W-300W


**40%**  
HIGH TRANSPARENCY

**72**  
HALF CELLS

**30 YEARS**  
Performance Warranty


up to **30 YEARS\***  
Product Warranty

\*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.



- Protects crops from heavy rain, hail, and wind
- Provides more stable temperature and humidity for crops
- Suitable for installation on greenhouse roofs
- 40% light transmission for homogeneous light distribution under the module
- Highly reliable and durable under mechanical loads

## OUR PERFORMANCE WARRANTY



## SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730  
Regular Production Surveillance  
www.tuv.com  
ID 1111257249

IEC 62716 (Ammonia corrosion)  
IEC 61701 (Salt mist corrosion)  
IEC 60068 (Sand and dust)  
IEC 62804 (PID resistance)



LID  
RESISTANT



PID  
RESISTANT



SALT CORROSION  
RESISTANT



SAND  
RESISTANT



AMMONIA  
RESISTANT




HIGHLY STABLE  
AND TOUGH

www.ae-solar.com

# AE CMD-72BD 280W-300W

N-TYPE TOPCON TECHNOLOGY PV MODULE

BIFACIAL • DOUBLE-GLASS



## Electrical specifications (STC\*):

|                            | $P_{max}$ (Wp) | 280   | 285   | 290   | 295   | 300   |
|----------------------------|----------------|-------|-------|-------|-------|-------|
| Nominal max. power         | $P_{max}$ (Wp) | 280   | 285   | 290   | 295   | 300   |
| Maximum operating voltage  | $V_{MPP}$ (V)  | 21.36 | 21.62 | 21.87 | 22.13 | 22.39 |
| Maximum operating current  | $I_{MPP}$ (A)  | 13.11 | 13.18 | 13.26 | 13.33 | 13.40 |
| Open-circuit voltage       | $V_{oc}$ (V)   | 25.26 | 25.59 | 25.91 | 26.24 | 26.56 |
| Short-circuit current      | $I_{sc}$ (A)   | 14.03 | 14.10 | 14.17 | 14.23 | 14.30 |
| Module efficiency          | $\eta$ (%)     | 14.36 | 14.62 | 14.87 | 15.13 | 15.39 |
| Power tolerance            | (W)            | 0~+5  |       |       |       |       |
| Maximum system voltage     | (V)            | 1500  |       |       |       |       |
| Maximum series fuse rating | (A)            | 25    |       |       |       |       |

\*STC: Standard Test Conditions (irradiance 1000 W/m<sup>2</sup>, cell temperature 25°C and air mass of AM1.5), measurement tolerance P<sub>max</sub>: ±3%

## Electrical specifications (NMOT\*):

|                           | $P_{max}$ (Wp) | 212   | 216   | 220   | 224   | 228   |
|---------------------------|----------------|-------|-------|-------|-------|-------|
| Nominal max. power        | $P_{max}$ (Wp) | 212   | 216   | 220   | 224   | 228   |
| Maximum operating voltage | $V_{MPP}$ (V)  | 19.70 | 19.98 | 20.24 | 20.49 | 20.75 |
| Maximum operating current | $I_{MPP}$ (A)  | 10.76 | 10.81 | 10.87 | 10.93 | 10.99 |
| Open-circuit voltage      | $V_{oc}$ (V)   | 23.73 | 24.05 | 24.39 | 24.70 | 25.01 |
| Short-circuit current     | $I_{sc}$ (A)   | 11.31 | 11.37 | 11.42 | 11.48 | 11.54 |

\*NMOT: Normal Module Operating Temperature (irradiance 800 W/m<sup>2</sup>, ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

## Bifacial electrical specifications

| Max. power front-side<br>$P_{max front}$ (Wp) | 280                  | 285                  | 290                  | 295                  | 300                  |
|---|----------------------|----------------------|----------------------|----------------------|----------------------|
| Backside Power Gain                           | 5% 10% 5% 10% 5% 10% | 5% 10% 5% 10% 5% 10% | 5% 10% 5% 10% 5% 10% | 5% 10% 5% 10% 5% 10% | 5% 10% 5% 10% 5% 10% |
| Total equivalent power<br>$P_{max equ}$ (Wp)  | 294 308              | 299 314              | 305 319              | 310 325              | 315 330              |
| Module efficiency<br>$\eta$ (%)               | 15.08 15.80          | 15.35 16.08          | 15.62 16.36          | 15.89 16.64          | 16.15 16.92          |

\*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

## Mechanical and design specification

|                             |  |
|-----------------------------|--|
| Cell type                   | n-Type TOPCon technology, half-cut cells             |
| No. of cells                | 72   |
| Transparency                | 40%  |
| Bifaciality                 | 80% +/- 5%   |
| Front cover                 | 2.0 mm glass, high transmission, AR coated, tempered |
| Encapsulation               | POE  |
| Back cover                  | 2.0 mm white glazed glass, tempered                  |
| Junction box                | IP68 rated, 3 bypass diodes                          |
| Frame                       | 30 mm anodized aluminium alloy                       |
| Cable (Including Connector) | 1 x 4 mm <sup>2</sup> , 350 mm length or customized  |
| Connectors                  | MC 4 / MC 4 compatible                               |
| Dimension                   | 1721 mm x 1133 mm x 30 mm                            |
| Weight                      | 23 kg  |
| Hail resistance             | Max. Ø 25 mm at 23 m/s                               |
| Wind load                   | 2400 Pa or 244 kg/m <sup>2</sup>                     |
| Snow load                   | 5400 Pa or 550 kg/m <sup>2</sup>                     |
| Fire rating                 | Class A (according to UL 790)                        |

## Temperature ratings

|                                |              |
|--------------------------------|--------------|
| Operating temperature          | -40 to +85°C |
| Temp. coefficient of $P_{max}$ | -0.30 %/°C   |
| Temp. coefficient of $V_{oc}$  | -0.25 %/°C   |
| Temp. coefficient of $I_{sc}$  | 0.046 %/°C   |
| Nom. operating cell temp. NOCT | 42 ± 2°C     |

## Packaging information

|                         |                             |
|-------------------------|-----------------------------|
| Packaging configuration | 36 pcs / pallet             |
| Loading capacity        | 936 pcs / 40 HQ             |
| Size / Pallet           | 1755 mm x 1140 mm x 1245 mm |
| Weight                  | 862 kg / pallet             |

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.