



PERFECT FOR AGRI-PV SOLUTIONS



Deutsche  
Qualität  
Garantiert

# 375W-395W

**Terra E** | CMD-96BD

**40%**  
HIGH TRANSPARENCY

**96**  
HALF CELLS

- ◆ Protects crops from heavy rain, hail, and wind
- ◆ Protects crops against frost and drought under extreme sunshine
- ◆ Suitable for installation on greenhouse roofs
- ◆ 40% light transmission for homogeneous light distribution under the module
- ◆ Highly reliable and durable under mechanical loads




Ver. 26.1.1

**30 YEARS**  
Performance Warranty

up to **30 YEARS\***  
Product Warranty

\*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. For extensions, please contact AESOLAR staff.

### OUR PERFORMANCE WARRANTY



**AESOLAR**

Since 2003



LID RESISTANT



PID RESISTANT



SALT CORROSION RESISTANT



SAND RESISTANT



AMMONIA RESISTANT






HIGHLY STABLE AND TOUGH

# AE CMD-96BD 375W-395W

PERFECT FOR AGRI-PV SOLUTIONS

BIFACIAL • DOUBLE-GLASS



## Electrical specifications (STC\*):

|                            | $P_{max}$ (Wp) | 375   | 380   | 385   | 390   | 395   |
|----------------------------|----------------|-------|-------|-------|-------|-------|
| Nominal max. power         | $P_{max}$ (Wp) | 375   | 380   | 385   | 390   | 395   |
| Maximum operating voltage  | $V_{MPP}$ (V)  | 28.24 | 28.49 | 28.54 | 28.76 | 28.85 |
| Maximum operating current  | $I_{MPP}$ (A)  | 13.28 | 13.34 | 13.49 | 13.56 | 13.69 |
| Open-circuit voltage       | $V_{oc}$ (V)   | 33.01 | 33.31 | 33.42 | 33.69 | 33.80 |
| Short-circuit current      | $I_{sc}$ (A)   | 14.20 | 14.26 | 14.40 | 14.47 | 14.61 |
| Module efficiency          | $\eta$ (%)     | 14.53 | 14.72 | 14.92 | 15.11 | 15.30 |
| Power tolerance            | (W)            |       |       | 0~+5  |       |       |
| Maximum system voltage     | (V)            |       |       | 1500  |       |       |
| Maximum series fuse rating | (A)            |       |       | 25    |       |       |

\*STC: Standard Test Conditions (irradiance 1000 W/m<sup>2</sup>, cell temperature 25°C and air mass of AM1.5), measurement tolerance  $P_{max}$ : ±3%

## Electrical specifications (NMOT\*):

|                           | $P_{max}$ (Wp) | 285   | 290   | 295   | 300   | 305   |
|---------------------------|----------------|-------|-------|-------|-------|-------|
| Nominal max. power        | $P_{max}$ (Wp) | 285   | 290   | 295   | 300   | 305   |
| Maximum operating voltage | $V_{MPP}$ (V)  | 26.49 | 26.84 | 27.00 | 27.31 | 27.50 |
| Maximum operating current | $I_{MPP}$ (A)  | 10.76 | 10.81 | 10.93 | 10.98 | 11.09 |
| Open-circuit voltage      | $V_{oc}$ (V)   | 30.97 | 31.38 | 31.61 | 31.99 | 32.22 |
| Short-circuit current     | $I_{sc}$ (A)   | 11.50 | 11.55 | 11.66 | 11.72 | 11.83 |

\*NMOT: Normal Module Operating Temperature (irradiance 800 W/m<sup>2</sup>, ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

## Bifacial electrical specifications


| Max. power front-side<br>$P_{max}$ front (Wp) | 375         | 380         | 385         | 390         | 395         |
|---|-------------|-------------|-------------|-------------|-------------|
| Backside Power Gain                           | 5% 10%      | 5% 10%      | 5% 10%      | 5% 10%      | 5% 10%      |
| Total equivalent power<br>$P_{max}$ equ (Wp)  | 394 413     | 399 418     | 404 424     | 410 429     | 415 435     |
| Module efficiency<br>$\eta$ (%)               | 15.26 15.98 | 15.46 16.20 | 15.66 16.41 | 15.87 16.62 | 16.07 16.83 |

\*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

## Mechanical and design specification

|                             |  |
|-----------------------------|--|
| Cell type                   | n-Type TOPCon technology, half-cut cells             |
| No. of cells                | 96   |
| Transparency                | 40%  |
| Bifaciality                 | 80 ± 5%  |
| Front cover                 | 2.0 mm glass, high transmission, AR coated, tempered |
| Encapsulation               | POE  |
| Back cover                  | 2.0 mm transparent glass, tempered                   |
| Junction box                | IP68 rated, 2 bypass diodes                          |
| Frame                       | 30 mm anodized aluminium alloy                       |
| Cable (Including Connector) | 1 x 4 mm <sup>2</sup> , 350 mm length or customized  |
| Connectors                  | MC 4 / MC 4 compatible                               |
| Dimension                   | 2278 mm x 1133 mm x 30 mm                            |
| Weight                      | 31 kg  |
| Hail resistance             | Max. Ø 25 mm at 23 m/s                               |
| Wind load                   | 2400 Pa or 244 kg/m <sup>2</sup>                     |
| Snow load                   | 5400 Pa or 550 kg/m <sup>2</sup>                     |
| Fire rating                 | Class A (according to UL 790)                        |


## Packaging information



## Temperature ratings

|                                |              |
|--------------------------------|--------------|
| Operating temperature          | -40 to +85°C |
| Temp. coefficient of $P_{max}$ | -0.29 %/°C   |
| Temp. coefficient of $V_{oc}$  | -0.25 %/°C   |
| Temp. coefficient of $I_{sc}$  | 0.046 %/°C   |
| Nom. operating cell temp. NOCT | 42 ± 2°C     |

## SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730  
Regular Production Surveillance  
www.tuv.com

IEC 62716 (Ammonia corrosion)  
IEC 61701 (Salt mist corrosion)  
IEC 60068 (Sand and dust)  
IEC 62804 (PID resistance)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.