

# 440W-460W

MD-120

**21.35%**  
MAXIMUM EFFICIENCY

**120**  
HALF CELLS

- ◆ Established durability and yield data
- ◆ High flexibility with BOM




Ver. 25.5.1

**30 YEARS**  
Performance Warranty

up to **30 YEARS\***  
Product Warranty

\*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.

## OUR PERFORMANCE WARRANTY



LID  
RESISTANT



PID  
RESISTANT



SALT CORROSION  
RESISTANT



SAND  
RESISTANT



AMMONIA  
RESISTANT






HIGHLY STABLE  
AND TOUGH

# AE MD-120 440W-460W

P-TYPE PERC TECHNOLOGY

MONO-FACIAL PV MODULE



## Electrical specifications (STC\*):

|                            |                |       |       |       |       |       |
|----------------------------|----------------|-------|-------|-------|-------|-------|
| Nominal max. power         | $P_{max}$ (Wp) | 440   | 445   | 450   | 455   | 460   |
| Maximum operating voltage  | $V_{MPP}$ (V)  | 34.62 | 34.87 | 35.13 | 35.38 | 35.60 |
| Maximum operating current  | $I_{MPP}$ (A)  | 12.71 | 12.76 | 12.81 | 12.86 | 12.92 |
| Open-circuit voltage       | $V_{oc}$ (V)   | 41.35 | 41.66 | 41.98 | 42.29 | 42.60 |
| Short-circuit current      | $I_{sc}$ (A)   | 13.47 | 13.52 | 13.57 | 13.62 | 13.67 |
| Module efficiency          | $\eta$ (%)     | 20.42 | 20.65 | 20.88 | 21.11 | 21.35 |
| Power tolerance            | (W)            | 0~+5  |       |       |       |       |
| Maximum system voltage     | (V)            | 1500  |       |       |       |       |
| Maximum series fuse rating | (A)            | 25    |       |       |       |       |

\*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance  $P_{max}$ : ±3%

## Mechanical and design specification


|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| Cell type                   | Gallium-doped mono c-Si PERC, half-cut cells         |
| No. of cells                | 120                                                  |
| Front cover                 | 3.2 mm glass, high transmission, AR coated, tempered |
| Encapsulation               | EVA                                                  |
| Back cover                  | White backsheet                                      |
| Junction box                | IP68 rated, 3 bypass diodes                          |
| Frame                       | 30 mm anodized aluminium alloy                       |
| Cable (Including Connector) | 1 x 4 mm², 350 mm length or customized               |
| Connectors                  | MC 4 / MC 4 compatible                               |
| Dimension                   | 1902 mm x 1133 mm x 30 mm                            |
| Weight                      | 22.5 kg                                              |
| Hail resistance             | Max. Ø 25 mm at 23 m/s                               |
| Wind load                   | 2400 Pa or 244 kg/m²                                 |
| Snow load                   | 5400 Pa or 550 kg/m²                                 |

## Electrical specifications (NMOT\*):

|                           |                |       |       |       |       |       |
|---------------------------|----------------|-------|-------|-------|-------|-------|
| Nominal max. power        | $P_{max}$ (Wp) | 331   | 335   | 338   | 342   | 345   |
| Maximum operating voltage | $V_{MPP}$ (V)  | 32.60 | 32.80 | 33.00 | 33.20 | 33.40 |
| Maximum operating current | $I_{MPP}$ (A)  | 10.17 | 10.21 | 10.25 | 10.29 | 10.34 |
| Open-circuit voltage      | $V_{oc}$ (V)   | 38.80 | 39.00 | 39.20 | 39.40 | 39.60 |
| Short-circuit current     | $I_{sc}$ (A)   | 10.78 | 10.82 | 10.86 | 10.90 | 10.94 |

\*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

## Packaging information



## Temperature ratings

|                                |              |
|--------------------------------|--------------|
| Operating temperature          | -40 to +85°C |
| Temp. coefficient of $P_{max}$ | -0.35 %/°C   |
| Temp. coefficient of $V_{oc}$  | -0.275 %/°C  |
| Temp. coefficient of $I_{sc}$  | 0.045 %/°C   |
| Nom. operating cell temp. NOCT | 45 ± 2°C     |

## SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730  
Regular Production Surveillance  
www.tuv.com

IEC 62716 (Ammonia corrosion)  
IEC 61701 (Salt mist corrosion)  
IEC 60068 (Sand and dust)  
IEC 62804 (PID resistance)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.



**AESOLAR**

Since 2003

+49 8231 978268 0  
sales@ae-solar.com  
www.ae-solar.com

**AESOLAR**  
Senefelderstraße 23  
86368 Gersthofen, Germany